This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

C11D 17/00, 3/395, 3/40

(11) International Publication Number:

WO 99/40170

A1

(43) International Publication Date:

12 August 1999 (12.08.99)

(21) International Application Number:

PCT/EP99/00325

(22) International Filing Date:

19 January 1999 (19.01.99)

(30) Priority Data:

98300792.3

4 February 1998 (04.02.98)

(74) Agent: TANSLEY, Sally, Elizabeth; Unilever PLC, Patent Dept., Colworth House, Shambrook, Bedford MK44 1LQ (GB).

Devai u. 26-28, H-1134 Budapest XIII (HU). PUERARI,

Francesco, Maria [IT/IT]; Lever Development Centre. Via Lever Gibbs, 3/a, 1-26841 Casalpusterlengo (IT).

TUMMIOLO, Roberto [IT/IT]; Lever Development Centre, Via Lever Gibbs, 3/a, 1-26841 Casalpusterlengo (IT).

(71) Applicant (for AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT UG ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).

(71) Applicant (for all designated States except AU BB CA CY GB GD GH GM IE IL IN KE I.C LK LS MN MW NZ SD SG SL SZ TT UG US ZW): UNILEVER N.V. [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Mumbai 400 20, Maharashtra (IN).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BOLZONI, Giuseppe, Vincenzo [IT/IT]; Lever Development Centre, Via Lever Gibbs, 3/a, I-26841 Casalpusterlengo (IT). MORRIS, Ronald, Meredith [GB/HU]; Unilever Magyarorszag KFT,

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: LAVATORY CLEANSING COMPOSITIONS

(57) Abstract

A lavatory cleansing block comprising: a) a particulate bleaching agent or precursor therefore, and b) a dyestuff on a particulate, non-bleaching carrier.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	C.	
AM	Armenia	FI	Finland	LT	Lithuania	SI	Slovenia
AT	Austria	FR	France	LU		SK	Slovakia
AU	Australia	GA	Gabon	LV	Luxembourg Latvia	SN	Senegal
AZ.	Azerbaijan	GB	United Kingdom	MC	Monaco	SZ	Swaziland
BA	Bosnia and Herzegovina	GE	Georgia	MD		TD	Chad
B	Barbados	GH	Ghana	MG	Republic of Moldova	TG	Togo
E	Belgium	GN	Guinea	MK	Madagascar	TJ	Tajikistan
F	Burkina Faso	GR	Greece	WIK	The former Yugoslav	TM	Turkmenistan
C	Bulgaria	HU	Hungary	ML	Republic of Macedonia Mali	TR	Turkey
J	Benin	IE	ireland	MN		TT	Trinidad and Tobago
R	Brazil	IL.	Israel	MR	Mongolia	UA	Ukraine
Y	Belarus	IS	Iceland	MW	Mauritania	UG	Uganda
A	Canada	IT	Italy	MX	Malawi Mexico	US	United States of Americ
F	Central African Republic	JP	Japan	NE		UZ	Uzbekistan
G	Congo	KE	Kenya	NL	Niger Netherlands	VN	Viet Nam
H	Switzerland	KG	Kyrgyzstan	NO		YU	Yugoslavia
ľ	Côte d'Ivoire	KP	Democratic People's	NZ	Norway	ZW	Zimbabwe
M	Cameroon		Republic of Korea	PL	New Zealand		
N	China	KR	Republic of Korea	PT	Poland		
U	Cuba	KZ	Kazakstan	RO	Portugal		
Z	Czech Republic	LC	\ Saint Lucia	RU	Romania		
E	Germany	Li	Liechtenstein	SD	Russian Federation		
K	Denmark	LK	Sri Lanka	SE	Sudan		
E	Estonia	LR	Liberia	3E	Sweden		

LAVATORY CLEANSING COMPOSITIONS

Technical Field

This invention is concerned with improvements in and relating to lavatory cleansing compositions. More particularly, the invention is concerned with solid lavatory cleansing compositions which may be used to impart cleansing and/or other components to the flush water of a lavatory or urinal by placement of the composition in the cistern of the lavatory or urinal.

Background to the Invention

- The use of solid slow-release compositions to impart cleansing and/or other components to the flush water of a lavatory or urinal is well known. Such compositions may, for example, be immersed in the water of a lavatory cistern either free-standing form or in containerised form (i.e., in a dispensing container which allows for release of components of the solid composition in solution in water in a more or less metered fashion, on flushing of the cistern).
- Alternatively, the solid composition may be held under the 25 rim of a toiler, in a suitable holder, for intermittent contact of the solid material with flush water.

For convenience these two approaches will be referred to as 'cistern-blocks' and 'rim-blocks' herein and known

30 collectively as 'toilet-blocks'. Such blocks produce foam, often produce a pleasing odour and can have germicidal properties.

WO 99/40170

- 2 -

Solid lavatory cleansing compositions typically comprise a surfactant component, generally together with one or more fillers or builders (e.g. inorganic salts such as sodium 5 sulphate, sodium chloride etc). Commonly, such compositions also contain a perfume, a dyestuff and, frequently, dissolution retarding material.

In recent years it has become commonplace for toilet blocks to contain a halogen release agent or other bleaching agent. 10 From EP 0206725 it is clear that halogen release agents are, by their nature, powerful chemically reactive species, serving as halogenating or oxidising agents and it is consequently difficult to incorporate bleach-sensitive components such as perfumes and dyestuffs into blocks which 15 contain bleaching agents.

It is, however, desirable to be able to determine rapidly when bleach is present in a block and thereby distinguish it 20 from blocks which do not contain bleach. Several possible ways of providing a visual indication that a block contains bleach can be envisaged: one might for example make the block a particular shape or mark the surface of the block with embossed pattern. While it would be desirable to 25 incorporate a colouring agent into a bleach-containing block this is not generally possible due to the interaction of the colour and the bleaching agent.

In the related art of liquid toilet bleaches, it has been 30 suggested to colour formulations by means of suspended pigment particles. These retain their colour in the presence of the bleaching agent and provide a visual means of identifying where a product has been used as well as

rough indication of dilution. Unfortunately, n quality sanitary porcelain is prone to form on its surface into which the pigment particles yiding a clear visible indication that surface are present. As a result, the use of pigments that not met with commercial success.

tion of the Invention

nined that improved toilet blocks can be ich comprise: a particulate bleaching agent (or) and a dyestuff on a particulate carrier other ing agent. This invention is of particular ad in in-cistern blocks.

the present invention provides a slow-release nsing block comprising:

ulate bleaching agent or precursor therefore,

ff on a particulate, non-bleaching carrier.

g the bleaching agent and the dyestuff in this possible to produce a block which provides a ation that a bleaching agent is present in the tinct speckled pattern thus the present ther provides the use of coloured speckles tory cleansing block to indicate the presence g agent.

Detailed Description of the Invention

5 In order that the invention may be further understood the following description details preferred and optional features of the invention.

Dyestuff and Carrier

10

Typically, blocks according to the present invention comprise 1-15% wt, more preferably 2-10% of a dyestuff on a carrier.

- Preferably the dye stuff is water dispersible, more preferably the dye is water soluble. Dyes that are blue or green are particularly suitable for indicating that bleach is present. We have determined that 'Sudangelb 150' (TM) ex. Sandoz is an acceptable colouring agent as are Colanyl
- 20 Green (TM) ex Hoechst P. Green (CI 74260) and Dispers Blue (TM) ex BASF. Particularly preferred colouring agent include pigments such as pigment blue 15 having a colour index of 74160.
- 25 Typically the dye stuff is present from 0.05 to 0.5 wt % of the total weight of the dyestuff/carrier granule.

It is preferred if the particulate non-bleaching carrier is water soluble. Water soluble in the context of the

30 invention is a solubility of at least 1g per 100 cc of water at 20°C. WO 99/40170

It is preferred if the particulate non bleaching carrier is selected from sodium carbonate, sodium sulphate, magnesium sulphate, or sodium chloride, particularly preferred is sodium carbonate.

5

30

The particulate non bleaching carrier is preferably present from 93% to 99% wt% of the dyestuff/carrier granule.

It is advantageous if the dyestuff/carrier granule further
comprises a binder such as a polycarylate a preferred binder
is an acrylic maleic copolymer. The binder is preferably
present from 0.1 to 1% wt of the dyestuff/carrier granule.

The dyestuff/carrier granules preferably have a particle size distribution between 100 and 1000 microns and a bulk density of 900 and 1150 g/l.

Bleaching Agents

Typically the blocks comprise up to 50% by weight of an at least sparingly water soluble bleaching agent. Typically levels of bleaching agents are 2-30% wt on product. For the purposes of the present specification the term bleaching agent is used to mean both a bleaching agent and a precursor which produces a bleaching agent unless the context demands otherwise.

Suitable bleaching agents active-halide and active-oxygen bleaching agents, particularly the so-called 'halogen release agents'.

Chlorine bleaching agents are preferred. Suitable water-soluble, active chlorine, bleaching agents used in

accordance with the invention include chlorinated cyanurates, phthalimides, p-toluence sulphonamides, azodicarbonamides, hydantoins, glycoluracils, amines and melamines. The alkali metal salts of cyanurates are preferred.

A particularly preferred bleaching agent is sodium dichlorocyanurate (NaDCCA). The bleaching agent is typically present in an amount of 10-30% and most preferably at around 25%. Oxidan DCN/WSG (TM) ex Sigma has been found to be a suitable bleaching agent.

Surfactants

Preferably, the composition will also contain a surfactant component which may be anionic or nonionic in nature. The surfactant serves to provide a cleansing and foaming effect.

Preferably, the surfactant component comprises one or more anionic surface active agents, optionally in combination with one or more nonionic surface active agents. Suitable anionic surface active agents include alkali metal or ammonium alkylaryl sulphonates (especially alkyl benzene sulphonates), alkane sulphonates, alkyl sulphates and sarcosinates.

We have determined that improved foaming properties are obtained by the use of a surfactant system which comprises primary alkyl sulphate (PAS) together with other anionic surfactants. Preferably the present invention provides a lavatory block comprising 1-15% wt (more preferably 1-5% wt) of a primary alkyl sulphate and 15-50%wt (more preferably 30-50%wt) of other anionic surfactants. We have determined

that the use of this mixed surfactant system is advantageous in that it reduces the stickiness of the block during manufacture. The blocks with 1-5% PAS show improved wear characteristics.

5

10

Preferably the other anionic surfactants are sulphonates. Suitable sulphonates include alkyl benzene sulphonate (ABS). It is believed that the combination of relatively low levels of PAS together with higher levels of ABS promotes the foaming and the perfume delivery from the block. PAS is also believed to be environmentally more acceptable than alkyl benzene sulphonate.

Suitable nonionic surfactants include polyethoxylated fatty alcohols, polyethoxylated fatty acids, polyethoxylated alkyl phenols, amine oxides and ethylene oxide/propylene oxide block copolymers.

The total amount of surfactant when present, may lie within wide limits. In practice, the surfactant will generally be for 10 to 70% by weight of the composition, but more preferable that surfactant comprises from 20 to 50% by weight thereof.

25 Process Aids

30

As will be described in further detail below extrusion is the preferred method of manufacture. Optionally, the blocks according to the invention further comprise a processing aid to assist in extrusion. Suitable processing aids include oils (including both mineral and silicone oils), esters (other than those derived from ethylenically unsaturated carboxyl group containing monomers) and polybutene.

One particularly suitable processing aid is an alkoxylated alcohol. It is preferred that the alkoxylated alcohol is an ethoxylated alcohol. The preferred level of alkoxylated alcohol is 0.75-2% wt. The preferred ethoxy chain length is 40-60 with an average ethoxy chain length of around 50 being preferred. Suitable materials include Empilan KM 50/KF (TM) ex. Albright & Wilson. Another suitable process aid is a PEG monostearate. PEG 4000 Monostearate (100%) ex DAC is a suitable raw material. It is believed that an effect of the process aid is to make the block harder and easier to cut from an extruded billet.

Fillers

15

Typically, blocks according to the present invention comprise 0 to 50% by weight of an inert non-polymeric and/or electrolyte filler. Preferably blocks contain 5-50%wt, more preferably 10-30% of filler.

20

Suitable fillers include one or more of urea, sodium, magnesium and calcium carbonates, sodium chloride, borax, talc and sodium, magnesium and calcium sulphates. Preferred ionic fillers include sodium sulphate. Preferred inert,

25 non-polymeric fillers include calcium carbonate.

Typical levels of total filler range from 10-40%wt on product in total.

It has been found useful, for ease of formulation and to ensure complete solubility of in-cistern blocks, to employ 10-30%wt of an ionic filler as the sole filler present.

- 9 -

For mixed filler systems, preferred levels of filler are 10-20% wt on product of ionic filler and 10-20% on product of inert filler. It is particularly preferred to use an approximately 50:50 mixture of sodium sulphate and calcium carbonate as the filler. For mixed filler systems typical levels in product are 15% wt of each of calcium carbonate and sodium sulphate.

Perfume

10

Preferably, the blocks comprise 2-15%wt of a hydrophobic oily liquid perfume. The blocks more preferably comprise, 2-10%, more preferably 3-6% wt of the perfume. Levels of around 4% wt perfume are particularly preferred. This oily perfume is typically of the kind described in the European patent application EP 167,210. It will be understood that the liquid oily perfume must be stable in the presence of the water-soluble, active chlorine, bleaching agent. Suitable oily perfumes can be easily selected by testing them in combination with the water-soluble, active chlorine, bleaching agent.

Examples of suitable bleach-stable perfumes are Verdeo 898, Bonanza 048 and Ponderosa 431 all ex IFF, and LB 132 ex

Quest. Particularly preferred perfumes are Icebreaker Super Mod, Oxygen Supra Mod, Motebianco Supra and lemonfit Supra (all TM) ex Givaudan Roure. The most preferred perfume is Green Tank Harder (TM) ex. Givaudan Roure.

Minors

- Minor components will generally be present but are optional. These include colouring agents, and/or whiteners. These materials should be chosen such that they are compatible with the bleaching agent and do not react therewith to a significant extent. Titanium dioxide is an acceptable whitener. Levels of colouring agents and/or whiteners as typically below 5% wt.
- Further enhancement of the product may be obtained by the additional use of chelating agent, sequestrant or water
 15 softening agent such as ethylene diamine tetra-acetic acid or a derivative thereof, nitrolotriacetic acid, phosphonates of polyphosphates, metasilicates, boroheptonates, s.s-thylene-diamino disuccinate, dipicolinic acid, 2-phosphonobutane-1,2,4-tricarboxylic acid, or lower molecular weight polymeric materials capable of inhibiting crystal growth. Further reducing agents, such as alkali metal metabisulphates may be present to assist in the reduction of staining due to metals such as iron.
- 25 An optional minor component is a foam-boosting surfactant. Suitable surfactants include amine oxides.

Polymers

A water-insoluble, gelling polymers may be used in compositions of the invention, these are polycarboxylic acids derived from one or more ethylenically unsaturated

20

carboxyl group-containing monomers, especially ethylenically unsaturated carboxylic acids such as acrylic acid or maleic acid.

Suitable polymers include polyacrylic acid, polymaleic anhydride and copolymers of either of the aforementioned with ethylene, styrene and methyl vinyl eter.

Typical polymers are polyacrylic acid and acrylic

acid/maleic acid copolymers. In practice the polymers are employed in the form of acids, but can also be employed as salts, e.g., alkali metal salts such as the sodium salt. The use of the polymer salts is advantageous if it is required to reduce dust production during formulation and manufacture.

If present it is preferred that the polymer is cross-linked. The cross-linked polyacrylate polymers are generally characterised as acrylic acid polymers which are cross-linked with an additional monomer or monomers in order to exhibit an effective molecular weight of one to seven million g/mole. The average formula weight for a polymer sub-unit is preferably of the order of 60-120 g/mole.

The polymer is suitably present in an amount of from 0.5 to 20% by weight, more preferably from 1 to 5% by weight, most preferably around 2-3% by weight thereof. Polygel DB (TM) ex 3V Sigma, a cross-linked high molecular weight polyacrylate, has been found to be a suitable material at an inclusion level of around 2-3%wt.

WO 99/40170

- 12 -

Process

20

25

30

Compositions in accordance with the invention may be produced by a variety of routes. For example, they may be prepared by a so-called "hot-melt" process comprising melting the fusible constituents of the block either alone and then adding other components in admixture with non-10 fusible components, and subsequently casting the melt into moulds. More preferably, however, compositions in accordance with the invention are formed into the desired final shape by a compression technique, i.e., a technique involving the steps of forming a mixture of the ingredients 15 of the compositions and then compressing that mixture into the desired shape.

An especially preferred process is an extrusion process in which the mixture of the components is extruded into a solid bar or rod which is subsequently cut into pieces of the desired size. In this connection, it may be noted that when the compositions of the invention are used as free-standing lavatory cleansing blocks, these suitably have a weight from 30 to 150 gms. When extruding a solid composition it is generally advantageous, as noted above, that some lubricant component or process aid be present to facilitate extrusion.

Compositions in accordance with the invention may also be formed into the final desired shape by a tabletting technique.

As used herein the term block is not intended to limit the shape of the eventual product. For cistern blocks the rod is cut into lengths which are short relative to their diameter.

5 Preferred Compositions

Preferred embodiments of the invention provide a slow release lavatory cleansing block comprising:

- 0 a) 2-30% wt of a halogen release agent,
 - b) 2-15% wt of an oily liquid perfume, and
 - c) 1-5% wt of a water dispersible dyestuff on a particulate, non bleaching carrier.
- 15 Particularly preferred compositions are:
 - a) 1-5% wt primary alkyl sulphate
 - b) 30-50% wt alkyl benzene sulphonate
- 20 c) 10-30% wt NaDCCA

30

- d) 10-30% wt sodium sulphate, calcium carbonate or a mixture thereof,
- e) 2-10% wt oily liquid perfume
- f) 1-5% wt of a water dispersible dyestuff on a particulate, non bleaching carrier.

The invention also provides a method of cleaning a lavatory or urinal using a block of a composition in accordance with the invention.

In order that the invention may well be understood, the following Examples are given by way of illustration only.

Examples

Toilet blocks were formed by an extrusion process in which the mixture of the components is extruded as a plastified mass through an aperture to form a billet and said billet is cut into tablets of appropriate size by means of a chain cutter.

1

10

The toilet blocks had the following formulation:

		Example .	
		wt %	
15			
	ABS ¹	37.0	
	PAS ²	4.5	
	NaDCCA	25.0	
	Sodium Sulphate	13.25	
20	Coloured Granules ³	2.5	
	Minors	to 100	

ABS¹ Nansa HS 80/LPF ex Albright & Wilson
25 PAS² PAS-Empicol LZ-V ex Albright & Wilson
Coloured granules³ sodium carbonate ex Crosfield

The blocks gave a satisfactory performance and did not stain the toilet.

CLAIMS

5

15

20

30

- A lavatory cleansing block comprising:
 - a) a particulate bleaching agent or precursor therefore, and
 - b) a dyestuff on a particulate, non-bleaching carrier.
- 10 2. A block according to claim 1 in which the particulate non-bleaching carrier is water soluble.
 - 3. A block according to either preceding claim, wherein the particulate non bleaching carrier comprises sodium carbonate, sodium sulphate, magnesium sulphate, or sodium chloride.
 - 4. A block according to any preceding claim in which the non bleaching carrier comprises sodium carbonate.
 - 5. A block according to any preceding claim, wherein the dyestuff on a particulate non bleaching carrier b) further comprises a binder.
- 25 6. A block according to claim 5 in which the binder ofb) is an acrylic maleic copolymer.
 - 7. A block according to any preceding claim in which the bleaching agent a) is a halogen release agent.
 - 8. A block according to any preceding claim in which the bleaching agent a) is selected from chlorinated cyanurates, phthalimides, p-toluence sulphonamides,

azodicarbonamides, hydantoins, glycoluracils, amines and melamines.

- A block according to any preceding claim in which the
 bleaching agent a) is sodium dichlorocyanurate
 (NaDCCA).
- A block according to any preceding claim, further comprising a processing aid selected from mineral oil,
 silicone oil, water insoluble esters other than those derived from ethylenically unsaturated carboxyl group containing monomers, polybutene and alkoxylated alcohols.
- 15 11. A block according to any preceding claim comprising:
 - a) 20-30% wt of a halogen release agent,
 - b) 2-15% wt of an oily liquid perfume, and
 - c) 1-5% wt of a water dispersible dyestuff on a particulate, non bleaching carrier.
 - 12. A block according to any preceding claim comprising:
 - a) 1-5% wt primary alkyl sulphate
- 25 b) 30-50% wt alkyl banzene sulphonate
 - c) 10-30% wt NaDCCA

20

- d) 10-30% wt sodium sulphate, calcium carbonate or a mixture thereof,
- e) 2-10% wt oily liquid perfume
- f) 1-5% wt of a water dispersible dyestuff on a particulate, non bleaching carrier.

13. Use of coloured speckles within a lavatory cleansing block to indicate the presence of a bleaching agent.

INTERNATIONAL SEARCH REPORT

PCT/EP 99/00325

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 511017/00 1110 11103/395 01103/40 According to imemational Patent Classification (IPC) or to both national classification and IPC 8. FIELDS SEARCHED Minimum documentation searched iclassification system followed by classification sympols: IPC 6 C110 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search iname of data base and "where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Category 1 Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No WO 97 47721 A (UNILEVER PLC.) 1.7-12 Α 18 December 1997 see claims 1-4 see page 3, line 1 - page 7, line 6 Α US 4 248 827 A (KITKO DAVID J.) 1-3.7-9. 13 3 February 1981 see column 2. line 5 - column 4, line 66 1,7,13 A GB 1 538 857 A (CIBA-GEIGY LTD.) 24 January 1979 see page 1. line 1 - page 3, line 83 A EP 0 206 725 A (JEYES GROUP LTD.) 1.7.12 30 December 1986 cited in the application see page 3. line 4 - page 5, line 24 see claims 1-7 -/--X Further documents are ested in the continuation of box C Patent taminy members are usted in annex Special categories of cited documents To later document published after the international filing date or priority date and not in conflict with the application but "A" document defining the general state of the last which is not cited to understand the principle of theory, underlying the considered to be of particular relevance invention "E" earlier document but published on or after the international "X" document of particular relevance; the claimed invention tuting date cannot be considered novel or cannot be considered to 1.º document which may throw doubts on pnormy claim(s) or which is cried to establish the publication gate of another crisison or other special reason (as specified). knyolve an inventive step when the document is taken alone "Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive, step when the document is complined with one or more other, such docu-"O" document referring to an oral disclosure, use, exhibition or ments, such combination being obvious to a person skilled in the art Other meens Iff Dubished phor to the international filing date but man then the phoray date claimed "5" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 19 April 1999 29/04/1999 D AND MARING ACCO es of the ISA Authorized officer European Patent Office PB 5818 Patentiaan 2 NL - 2280 HV RIBWER Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Serbetsoglou, A Fax (-31-70) 340-3016

1

INTERNATIONAL SEARCH REPORT

PCT/EP 99/00325

Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No
1	WO 94 26863 A (BLOCK DRUG CO. INC.)	1,7,8
	24 November 1994	
	see page 7. line 10 - page 9. line 26 see claims 1-4,12	
_		
A	GB 1 281 796 A (UNILEVER LTD.) 12 July 1972	1-4.7-9,
	see page 1, line 1 - page 2, line 104	13
A	WO 96 28536 A (JEYES GROUP PLC.) 19 September 1996	1,5-7
	see page 5; claims 1,2	
į		
!		
ļ		
	·	
	· ·	
	\	

INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/EP 99/00325

Patent document cited in search report		Publication gate	Patent tamily member(s)		Publication date
WO 97477	21 A	18-12-1997	AU	2899097 A	07-01-1998
			CA	2248093 A	18-12-1997
			EP	0906410 A	07-04-1999
US 42488	27 A	03-02-1981	CA	1118984 A	02-03-1982
			US	4308625 A	05-01-1982
GB 15388	57 A	24-01-1979	NONE		
EP 02067	25 A	30-12-1986	AT	98297 T	15-12-1993
			ΑU	585356 B	15-06-1989
			AU	5887486 A	18-12-1986
			CA	1300464 A	12-05-1992
			DE	3689368 D	20-01-1994
			GB	2178442 A,B	11-02-1987
			US	5610126 A	11-03-1997
WO 94268	53 A	24-11-1994	US	5578559 A	26-11-1996
			AU	692158 B	04-06-1998
			AU	6786694 A	12-12-1994
			BR	9406703 A	27-02-1996
			CA	2161411 A	24-11-1994
			€P	0698080 A	28-02-1996
			JP	9500664 T	21-01-1997
			NZ	266387 A	26-11-1996
		~	US	5763376 A	09-06-1998
GB 12817	96 A	12-07-1972	BE	763419 A	24-08-1971
			DE	2108186 A	07-10-1971
			FR	2078977 A	05-11-1971
			LU	60397 A	06-10-1971
			NL	7102207 A	26-08-1971
			ZA	7101044 A	27-09-1972
WO 96285	36 A	19-09-1996	AU	5011996 A	02-10-1996
			GB	2313129 A.B	19-11-1997